










Line - LED-Aufbauleuchte 230 V












▪ Aluminium gebürstet


	Farbe	Watt	Lichtfarbe	Lumen	Länge
79.60220.30	Aluminium	16 W	3000 K	2060 lm	580 mm
79.60221.30	Aluminium	26 W	3000 K	3100 lm	870 mm
79.60222.30	Aluminium	33 W	3000 K	4140 lm	1140 mm
79.60223.30	Aluminium	40 W	3000 K	5170 lm	1430 mm
79.60220.40	Aluminium	18 W	4000 K	2200 lm	580 mm
79.60221.40	Aluminium	26 W	4000 K	3300 lm	870 mm
79.60222.40	Aluminium	33 W	4000 K	4400 lm	1140 mm
79.60223.40	Aluminium	40 W	4000 K	5500 lm	1430 mm

- i**
- Kein Lagerartikel, Lieferzeit ca. 2 Woche.
 - Weitere Ausführungen auf Anfrage.

Line air - LED-Pendelleuchte 230 Volt





- Aluminium gebürstet
- Pendelaufhängung: 2000 mm
- Anschlussleitung: 2000 mm klar

	Farbe	Watt	Lichtfarbe	Lumen	Länge
79.60224.30	Aluminium	18 W	3000 K	2060 lm	580 mm
79.60225.30	Aluminium	26 W	3000 K	3100 lm	870 mm
79.60226.30	Aluminium	33 W	3000 K	4140 lm	1140 mm
79.60227.30	Aluminium	40 W	3000 K	5170 lm	1430 mm
79.60224.40	Aluminium	18 W	4000 K	2200 lm	580 mm
79.60225.40	Aluminium	26 W	4000 K	3300 lm	870 mm
79.60226.40	Aluminium	33 W	4000 K	4400 lm	1140 mm
79.60227.40	Aluminium	40 W	4000 K	5500 lm	1430 mm

- i**
- Kein Lagerartikel, Lieferzeit ca. 2 Woche.
 - Weitere Ausführungen auf Anfrage.

i Technische Informationen und Legende zu Ikonen ab Seite A-1.79.