












LED industrial and room lighting
Ceiling LED light - Vero ABR, Vero ABQ, Batao

VERO ABR - Recessed ceiling LED light 230 volt

 230V
 
 dimmable
  CRI 80
  IP43
  CE
 








 A+
  incl.
 




- dimmed with a trailing-edge phase angle dimmer
- Plexiglass cover: opal




	finish	watt	light colour	lumen	Index Ra	variation
79.61050.30	white	21 W	3000 K	1600 lm	>80	round

VERO ABQ - Recessed ceiling LED light 230 volt

 230V
 
 dimmable
  CRI 80
  IP43
  CE
 








 A+
  incl.
 




- dimmed with a trailing-edge phase angle dimmer
- Plexiglass cover: opal



	finish	watt	light colour	lumen	Index Ra	variation
79.61051.30	white	21 W	3000 K	1600 lm	>80	square

Batao - Ceiling surface mounted light 230 volt

 230V
 
 120°
  dimmable
  CRI >84
  CE
 

 A+
  incl.
 

- including power pack. Can be dimmed with a trailing-edge phase angle dimmer



	finish	watt	light colour	lumen	external dimensions Ø	angle
79.61073.30	white	12 W	3000 K	1090 lm	250 mm	120 °
79.61073.40	white	12 W	4000 K	1120 lm	250 mm	120 °
79.61070.30	white	18 W	3000 K	1567 lm	300 mm	120 °
79.61070.40	white	18 W	4000 K	1615 lm	300 mm	120 °

i Technical information and legend for icons (page A-1.79).