












# LED Industrie- und Raumbelichtung

## 3-Phasen-Stromschienenspot - T202, T204, T206

### T202 Light - 3PH-Strahler 230 Volt

 230V		 10-60°	<b>CRI</b> >80	 IP54	 50000 h	 180
			 A+			



- drehbar 180° / schwenkbar 350°
- Systemgarantie: 60 Monate

	Farbe	Watt	Lichtfarbe	Lumen	Index Ra	Winkel
76.34580.30	weiss	20 W	3000 K	1470 lm	>80	10 °
76.34582.30	weiss	20 W	3000 K	1470 lm	>80	60 °
76.34580.40	weiss	20 W	4000 K	1500 lm	>80	10 °
76.34581.40	weiss	20 W	4000 K	1500 lm	>80	30 °
76.34582.40	weiss	20 W	4000 K	1500 lm	>80	60 °

### T204 Light - 3PH-Strahler 230 Volt

 230V		 10-60°	<b>CRI</b> >80	 IP54	 50000 h	 180				 A+	
--	---	--	-------------------	--	---	---	---	--	---	--	---

	Farbe	Watt	Lichtfarbe	Lumen	Index Ra	Winkel
76.34583.30	weiss	31 W	3000 K	1940 lm	>80	10 °
76.34584.30	weiss	31 W	3000 K	1940 lm	>80	30 °
76.34585.30	weiss	31 W	3000 K	1940 lm	>80	60 °
76.34583.40	weiss	31 W	4000 K	1980 lm	>80	10 °
76.34584.40	weiss	31 W	4000 K	1980 lm	>80	30 °
76.34585.40	weiss	31 W	4000 K	1980 lm	>80	60 °

### T206 Light - 3PH-Strahler 230 Volt

 230V		 20-60°	<b>CRI</b> >80	 IP54	 50000 h	 180				 A+	
--	---	--	-------------------	--	---	---	---	--	---	--	---

	Farbe	Watt	Lichtfarbe	Lumen	Index Ra	Winkel
76.34587.30	weiss	41 W	3000 K	3050 lm	>80	20 °
76.34588.30	weiss	41 W	3000 K	3050 lm	>80	30 °
76.34589.30	weiss	41 W	3000 K	3050 lm	>80	60 °
76.34587.40	weiss	41 W	4000 K	3100 lm	>80	20 °
76.34588.40	weiss	41 W	4000 K	3100 lm	>80	30 °
76.34589.40	weiss	41 W	4000 K	3100 lm	>80	60 °

- i** Technische Informationen und Legende zu Ikonen (Seite A-1.79).
- Gehäuse auch in den Farben Schwarz, Silber.
  - Kein Lagerartikel, Lieferzeit ca. 3 Wochen.