

LED Profil lights

LED-Strip - OS64, Power, OS128

OS64 LED-Strip flex 24 volt DC



- LED per meter: 64
- LED point of intersection: all 125 mm

	watts/m	light colour	lumen/m	length
76.50302.30	11.0 W	3000 K	1800 lm	5000 mm
76.50302.40	11.0 W	4000 K	1800 lm	5000 mm



i For Aluminum profile:

- Angolo, Bano, Cover, Delta, Derby, Lighting, Lumino, Manico, Mano, Railo, Slim, Tango, Tec, UP Down, Veno
- Order the Profile separately (pages A-1.04 - A-1.14), power pack (page A-1.19), Lighting control (pages A-1.19.1 - A-1.21).

Power LED-Strip flex 24 Volt DC



- LED per meter: 240
- LED point of intersection: all 25 mm

	watts/m	light colour	lumen/m	length
76.50303.27	19.2 W	2700 K	1700 lm	5000 mm
76.50303.30	19.2 W	3000 K	1700 lm	5000 mm
76.50303.40	19.2 W	4000 K	1700 lm	5000 mm



i For Aluminum profile:

- Angolo, Cover, Delta, Lighting, Lumino, Manico, Mano, Railo, Slim, Tango, Tec, UP Down, Veno
- Order the Profile separately (pages A-1.04 - A-1.14), power pack (page A-1.19), Lighting control (pages A-1.19.1 - A-1.21).

OS128 LED-Strip flex 24 volt DC



- LED per meter: 128
- LED point of intersection: all 62 mm

	watts/m	light colour	lumen/m	length
76.50304.30	22.0 W	3000 K	3400 lm	5000 mm
76.50304.40	22.0 W	4000 K	3400 lm	5000 mm



i For Aluminum profile:

- Angolo, Cover, Lighting, Lumino, UP Down
- Order the Profile separately (pages A-1.08 - A-1.14), power pack (page A-1.19), Lighting control (pages A-1.19.1 - A-1.21).

i Technical information and legend for icons (page A-1.79).