

LED Profil lights

LED-Strip - Rayo, QL, TL Two-Light

Rayo LED-Strip flex 24 volt DC



- LED per meter: 120
- LED point of intersection: all 50 mm

	watts/m	light colour	lumen/m	length
76.50305.27	20.0 W	2700 K	2040 lm	5000 mm
76.50305.30	20.0 W	3000 K	2040 lm	5000 mm
76.50305.40	20.0 W	4000 K	2040 lm	5000 mm

i For Aluminium profile:

Angolo, Cover, Lighting, Lumino, Up Down

- Order the Profile separately (pages A-1.08 - A-1.14), power pack (page A-1.19), Lighting control (pages A-1.19.1 - A-1.21).



QL LED-Strip flex 24 volt DC



- LED per meter: 126
- LED point of intersection: all 50 mm

	watts/m	light colour	lumen/m	length
76.50306.27	22.0 W	2700 K	2750 lm	5000 mm
76.50306.30	22.0 W	3000 K	2750 lm	5000 mm
76.50306.40	22.0 W	4000 K	2750 lm	5000 mm

i For Aluminum profile:

Angolo, Cover, Delta, Lighting, Lumino, Up Down

- Order the Profile separately (pages A-1.08 - A-1.14), power pack (page A-1.19), Lighting control (pages A-1.19.1 - A-1.21).



TL LED-Strip flex Two-Light 24 volt DC



- LED per meter: 120
- LED point of intersection: all 100 mm

	watts/m	light colour	lumen/m	length
76.50307.00	9.6 W	3000 - 6000 K	576 lm	5000 mm

i For Aluminum profile:

Bano, Cover, Delta, Derby, Manico, Mano, Railo, Slim, Tango, Tec, Venno

- Order the Profile separately (pages A-1.04 - A-1.14), power pack (page A-1.19), Lighting control (page A-1.21).



TLM LED-Strip flex Two-Light 24 volt DC

- LED per meter: 120
- LED point of intersection: all 100 mm

	watts/m	light colour	lumen/m	length
76.50314.00	14.4 W	2300 - 5500 K	1480 lm	5000 mm

i For Aluminum profile:

Angolo, Bano, Cover, Delta, Lighting, Lumino, Manico, Railo, Slim, Tango, Tec, UP Down, Venno

- Order the Profile separately (pages A-1.04 - A-1.14), power pack (page A-1.19), Lighting control (pages A-1.21).

