

TLP LED-Strip flex Two-Light 24 volt DC



- LED per meter: 120
- LED point of intersection: all 50 mm

	watts/m	light colour	lumen/m	length
76.50308.00	19.2 W	2700 - 5900 K	1480 lm	5000 mm

i For Aluminum profile:

- Angolo, Bano, Cover, Delta, Lighting, Lumino, Manico, Railo, Slim, Tango, Tec, UP Down, Veno
- Order the Profile separately (pages A-1.04 - A-1.14), power pack (page A-1.19), Lighting control (pages A-1.21).



Onyx RGB-Strip flex 24 volt DC



- LED per meter: 120
- LED point of intersection: all 100 mm

	watts/m	light colour	length
76.50309.00	14.0 W	RGB	5000 mm

i For Aluminum profile:

- Angolo, Bano, Cover, Delta, Lighting, Lumino, Manico, Railo, Slim, Tango, Tec, UP Down, Veno
- Order the Profile separately (pages A-1.04 - A-1.14), power pack (page A-1.19), Lighting control (pages A-1.21).



Onyx RGBW-Strip flex 24 volt DC



- LED per meter: 120
- LED point of intersection: all 84 mm

	watts/m	light colour	length
76.50310.00	23.0 W	RGBW	5000 mm

i For Aluminum profile:

- Angolo, Bano, Cover, Delta, Lighting, Lumino, Manico, Railo, Slim, Tango, Tec, UP Down
- Order the Profile separately (pages A-1.05 - A-1.14), power pack (page A-1.19), Lighting control (pages A-1.21).



Rivo LED-Strip flex 24 volt DC



- LED per meter: 120
- LED point of intersection: all 100 mm

	watts/m	light colour	lumen/m	Index Ra	angle	length
76.50311.30	17.0 W	3000 K	1496 lm	Ra >90	120 °	5000 mm
76.50311.40	17.0 W	4000 K	1496 lm	Ra >90	120 °	5000 mm

i For Aluminum Profile:

- Chaidor Train
- Order the Profile separately (pages B-3.73 - A-1.19), power pack (page A-1.19), Lighting control (pages A-1.19.1 - A-1.21).

