

ER power supply 15 watt, 230/24 volt DC



- primary/secondary: clamp connection

	finish	watt	dimension
76.50400.11	white	15 W	lxwxh: 130x40x16 mm
76.50401.11	white	30 W	lxwxh: 142x45x27 mm
76.50402.11	white	60 W	lxwxh: 158x55x37 mm
76.50403.11	white	100 W	lxwxh: 230x60x37 mm



MW power supply 230/24 volt DC




- primary: cable 300 mm without plug
- secondary: 300 mm cable section with connector sleeves

	finish	watt	dimension
76.50404.00	white	150 W	lxwxh: 228x68x39 mm
76.50405.00	white	240 W	lxwxh: 244x68x39 mm
76.50406.00	white	320 W	lxwxh: 252x90x44 mm



Domi - LED-Controller 1- 10 volt 12/24 Volt




- dimnable over 1-10 volt interface
- Measures (lxwxh: 1 mm x 50 mm x 25 mm)

	finish	volt	watt	output current
76.50500.29	black	12/24 V	2x 120/240 W	2x 10 A

- i** Order dimmer 1-10 v separately E-No. 548280000.



Dila - LED Controller Dali 12/24 volt



- dimnable over Dali
- Measures (lxwxh: 150 mm x 50 mm x 25 mm)

	finish	volt	watt	output current
76.50501.29	black	12/24 V	2x 120/240 W	2x 10 A

- i** Order bushbutton switch separatelx E-No. 554521000.



- i**
 - Download the PROJEKTER as PDF file.
 - Technical information and legend for icons (page A-1.79).

- !** To be connected by an electricia.