


ER power supply 15 watt, 230/24 volt DC




Primary/Secondary: clamp connection

	finish	watt	dimension
76.50400.11	white	15 W	lxwxh: 130x45x17 mm
76.50401.11	white	30 W	lxwxh: 142x52x33 mm
76.50402.11	white	60 W	lxwxh: 256x30x16 mm
76.50403.11	white	100 W	lxwxh: 256x30x16 mm



MW power supply 230/24 volt DC




Primary cable 300 mm without plug

Secondary: 300 mm cable section with connector sleeves

	finish	watt	dimension
76.50404.00	white	150 W	lxwxh: 130x45x17 mm
76.50405.00	white	240 W	lxwxh: 142x52x33 mm
76.50406.00	white	320 W	lxwxh: 256x30x16 mm



Domi - LED Controller 1- 10 Volt 12/24 V



dimnable over 1-10 volt interface


Measures (lxwxh: 50 mm x 150 mm x 25 mm)

	finish	volt	watt	output current
76.50500.29	black	12/24 V	2x 120/240 W	2x 10 A

i Order dimmer 1-10 v separately E-No. 548280000



Dila - LED Controller Dali 12/24 volt



dimnable over Dali

Measures (lxwxh: 150 mm x 50 mm x 25 mm)

	finish	volt	watt	output current
76.50501.29	black	12/24 V	2x 120/240 W	2x 10 A

i Order bushbutton switch separatelx E-No. 554521000



i

- Download the PROJEKTER as PDF file
- Technical information and legend for icons (page A-1.79).

! To be connected by an electricia.