

LED Profil lights

Power pack - ER, MW

ER power supply 15 watt, 230/24 volt DC



- primary/secondary: clamp connection

	description	finish	watt	dimension
71.20055.11	assembled	white	15 W	lxwxh: 130x40x16 mm
76.50400.11	single item	white	15 W	lxwxh: 130x40x16 mm
71.20044.11	assembled	white	30 W	lxwxh: 142x45x27 mm
76.50401.11	single item	white	30 W	lxwxh: 142x45x27 mm
71.20046.11	assembled	white	60 W	lxwxh: 158x55x37 mm
76.50402.11	single item	white	60 W	lxwxh: 158x55x37 mm
71.20067.11	assembled	white	100 W	lxwxh: 230x60x37 mm
76.50403.11	single item	white	100 W	lxwxh: 230x60x37 mm



MW power supply 230/24 volt DC



- primary: cable 300 mm without plug
- secondary: 300 mm cable section with connector sleeves

	description	finish	watt	dimension
71.20048.00	assembled	white	150 W	lxwxh: 228x68x39 mm
76.50404.00	single item	white	150 W	lxwxh: 228x68x39 mm
71.20049.00	assembled	white	240 W	lxwxh: 244x68x39 mm
76.50405.00	single item	white	240 W	lxwxh: 244x68x39 mm
71.20050.00	assembled	white	320 W	lxwxh: 252x90x44 mm
76.50406.00	single item	white	320 W	lxwxh: 252x90x44 mm



- Download the PROJEKTER as PDF file.
 - Technical information and legend for icons (page A-1.79).

! To be connected by an electrician.