

Ontop S3 Tubes

- LED Lamp in T8 shape with G13 socket (included starter)
- for operation with standard ballast
- angle of reflected beam 120°
- operation with electronic ballast is not possible, not dimmable
- Measures (Ø): 26 mm
- 36 months warranty (irrespective of turn-on time)

	watt	light colour	lumen	Index Ra	angle	length
79.15000.40	23 W	4000 K	2350 lm	>80	120 °	1500 mm
79.15000.60	23 W	6000 K	2350 lm	>80	120 °	1500 mm



Ontop My Tubes "Milky" 230 V

	watt	light colour	lumen	Index Ra	angle	length
79.15003.40	23 W	4000 K	2200 lm	>80	120 °	1500 mm
79.15003.60	23 W	6000 K	2200 lm	>80	120 °	1500 mm



Ontop MYM Tubes 230 V

	watt	light colour	lumen	Index Ra	angle	length
79.14010.40	20 W	4000 K	2400 lm	>82	120 °	1200 mm
79.14010.60	20 W	6000 K	2400 lm	>82	120 °	1200 mm

	watt	light colour	lumen	Index Ra	angle	length
79.15010.40	30 W	4000 K	3800 lm	>82	120 °	1500 mm
79.15010.60	30 W	6000 K	3800 lm	>82	120 °	1500 mm



Ontop Basic Tubes 230 V

	watt	light colour	lumen	Index Ra	angle	length
79.14007.40	19 W	4000 K	2150 lm	>82	120 °	1200 mm

	watt	light colour	lumen	Index Ra	angle	length
79.15007.60	25 W	6000 K	3000 lm	>82	120 °	1500 mm



- i** Energy label (page A-1.91), RA-Faktor (page A-1.90), Lumen (page A-1.90, Light colour (page A-1.90).
- Fluorescent lamp 18 W = 590 mm23.23", 30 W = 895 mm35.24", 36 W = 1200 mm47.24", 58 W 1500 mm.59.06"
 - other Ontop S3 Tubes on request.
 - Mounting instructions: (page A-1.88).